


Legend Series

IntelligentScanner

IntelligentScanner specs

Size	112mm x 60mm x 30mm (not including lens)
Mounting	Four M4 threaded holes (on the back of unit), 7.9mm depth
Weight	170g/6oz (without lens or integrated light)
Power Requirements	24V DC, 210mA (or minimum 5W supply), regulated and isolated. Additional 5W required for integrated light option. Additional 30W required per DVT LED array light.
Operating Temperatures	Operating Temperature: 0-45° C, 32-113° F
Image Sensor	4.8mm x 3.6mm (1/3" format) CCD, 640 x 480 pixel resolution, 7.4µm x 7.4 µm pixels
Electronic Shuttering	10 µs – 1 second exposure times
Optics	CS mount standard, C mount-capable with included adaptor
External Port	RJ-45 for 10/100 Mbps Ethernet communications, 10 pin keyed modular connector for power and digital I/O
Digital I/O	24V DC regulated, 8 configurable inputs and outputs, NPN (current sinking) inputs, PNP (current sourcing) outputs, active high signals. Inputs can sink up to 1.5mA and outputs source a maximum of 50 mA
Certifications	CE certified



Note: All Units in mm.



The SmartImage Sensor Specialists

1670 Oakbrook Drive, Suite 330 • Norcross, Georgia 30093

Phone: (770) 449-4960 • Fax: (770) 449-3073

<http://www.dvtsensors.com>

©Copyright DVT Corporation 2002. All trademarks are the property of their respective owners